

DB2700 & DB3600

DEBRIS BLOWERS



**BI-DIRECTIONAL
DISCHARGE**



Bi-directional discharge.

**27"
OR 36"**

27" or 36" diameter fan available.

**DUAL CASTER
WHEELS**

Dual caster wheels and full width roller to prevent scalping.

DB2700 & DB3600 DEBRIS BLOWER SPECIFICATIONS

Model	DB2700	DB3600
Air Flow	4000 CFM approx. 225 MPH	7100 CFM approx. 220 MPH
Noise at operator seat	81 db	94 db
Blower Housing	31" split design for easy fan access	40" split design for easy fan access
Fan	27" diameter	36" diameter
Drive	540 RPM PTO belt drive	540 RPM PTO belt drive
PTO Shaft	2N Metric	14R heavy-duty
Belt Drive	4/3b Powerband	4-5L V-belts with automatic tensioner
Mounting	Tractor 3 point, cat. 1	Tractor 3 point, cat. 1
Caster Wheels	Heavy-duty 10" adjustable	Heavy-duty 10" adjustable
Anti-Scalp	Tough 3" diameter rollers	Tough 3" diameter rollers
Power Requirement	20-30 PTO horsepower minimum	30 PTO horsepower minimum
Weight	425 lbs.	825 lbs.
Length	43"	48"
Width	48"	64"
Height	36"	45"
Air-Flow Control	Bi-directional discharge (left or right) controlled from operator seat	Bi-directional discharge (left or right) controlled from operator seat

The manufacturer reserves the right to make changes in engineering, design and specifications or add improvements at any time without notice or obligation.



HARPER®
Goossen